



This easy-to-use 125 kHz HID card RFID reader is designed for secure system access such as accessing a POS system.

The easy-to-use 125 kHz HID-enabled RFID reader is designed with a fully plug&play USB interface. It is a perfect RFID reader to use as logon device to protect a system from unauthorized use.



Key Features

- ✓ Plug&play design
- ✓ Easy-to-use
- ✓ Designed with USB interface
- ✓ Read 125 kHz HID proximity cards

Technical Specifications

Power Requirements	5 V / 200 mA
Interfaces	USB (keyboard emulation)
Card Type	HID Proximity card Wiegand 26, 34, 35, 37 bits
Card Dimension	86 mm × 55 mm × 2 mm maximum
Dimension	65 mm × 99.5 mm × 26 mm
Housing	ABS
Weight	115 g
Operating Temperature	-10 °C to 55 °C
Operating Relative Humidity	10% to 90%



GAO RFID Inc.

A Member of GAO Group

Celebrating Over 15 Year of Innovation

Product Overview

125 kHz HID Card RFID Reader (211015)



GAO Group

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com