



***This RFID tag is generally used for personnel identification/authentication, access control, transit, parking, event attendance management, ticketing, card payment, and product identification***

This low frequency (LF) RFID tag has a key ring design and is generally used for personnel identification/ authentication, access control, transit, parking, event attendance management, ticketing, card payment, and product identification. The tag is encapsulated within ABS thus it is waterproof and shock resistant. This passive tag has several chip type options including TK4100, T5557, MF1S50, S70, Ti2048, Ti256, ICODE1, ICODE 2 and INSIDE 2 K. It offers a tested read range of 3 cm to 15 cm.



### **Key Features**

- ✓ Compact, durable and non-fading
- ✓ Waterproof, shock resistant
- ✓ Easy-to-carry
- ✓ A variety of styles and colors for selection
- ✓ ID code can be printed on the fob



**GAO RFID Inc.**

**A Member of GAO Group**

*Celebrating Over 15 Year of Innovation*

*Product Overview*

**125 kHz Key Fob RFID Tag (111007)**

## **Specifications**

Storage Capacity	512 bits
Read Time	1 ms to 2 ms
Read Distance	3 cm to 15 cm
Rewrite Times	> 100000
Housing Material	ABS
Packaging	Ultrasonic
Operating Temperature	-15 °C to 55 °C
Size	43.7 mm x 30.5 mm x 5.3 mm



**GAO RFID Inc.**

**A Member of GAO Group**

*Celebrating Over 15 Year of Innovation*

*Product Overview*

**125 kHz Key Fob RFID Tag (111007)**



## **GAO Group**

[GAORFID.com](http://GAORFID.com)

[GAOTek.com](http://GAOTek.com)

[GAORFIDAssetTracking.com](http://GAORFIDAssetTracking.com)

[GAOComm.com](http://GAOComm.com)

[GAOInstruments.com](http://GAOInstruments.com)

[GAOFiberOptics.com](http://GAOFiberOptics.com)

[GAOEmbedded.com](http://GAOEmbedded.com)

[GAOResearch.com](http://GAOResearch.com)

Toll Free (USA & Canada)

**1-877-585-9555**

All Other Areas

**416-292-0038**

Dial Ext.601 for Sales  
Ext.602 for Other Inquiries

[sales@GAORFID.com](mailto:sales@GAORFID.com)