

This 125kHz handheld RFID reader/writer has an IP54 protection rating allowing for robust operation even in harsh environmental circumstances.

This portable low frequency RFID reader/writer is appropriate for applications such as guard tour monitoring systems, remote equipment inspection management, goods delivery and transportation management. It allows for accurate, real-time data transmission and reads compatible RFID tags at distances from 20mm to 30mm.

## **Key Features**

- ✓ Light in weight
- ✓ User-friendly interface design
- ✓ Resistant to shock and dust

- ✓ Fast Tag Identification
- ✓ Long operating time
- ✓ Collects tag data without delay even at low temperature of -5°C





## **Technical Specifications**

Frequency	125kHz
Standard deployment	ASK Manchester coding, EM Compatible 64bits
Reading distance	20mm to 30mm
Time of identity	Less than 1s
Environmental sealing	IP54 Standard. Anti-shock / Dust-proof
Data interface	RS232
Power supply	Re-chargeable Lithium battery (1500mAh)
Power consumption	Less than 2W in reading state, 0W in idle state
Operating temperature	-5°C to 50°C
Dimensions	185mm x 70mm x 35mm







## **GAO Group**

Celebrating Over 15 Years of Innovation

GAORFID.com GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

**GAOInstruments.com** 

**GAOFiberOptics.com** 

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales Ext.602 for Other Inquiries

China: 86-519-80691090

86-519-80691089

sales@GAORFID.com