127044

Overview:

GAORFID SKU#127044 Waterproof beacon/tag operates at 2.45GHz, the SKU#127044 active tag is a new generation beacon that is loaded with Bluetooth 5.0 hardware platform, and supports to advertise standard iBeacon. The reading range between 127044 and compatible gateways/receivers could be up to 100 meters.

Main Features:

- ✓ Standard iBeacon, free band of 2.45GHz
- ✓ Bluetooth 4.0/5.0 chipset
- ✓ The max. 100 meters reading distance with SKU#217030 gateway or any other Bluetooth Featured devices (e.g. iPhones, Android smart devices, etc.)
- ✓ High Precise Temperature and Humidity sensor integrated
- ✓ Built-in Accelerometer/Vibration Sensor
- ✓ Ultra-low power consumption chipset nRF52 series
- ✓ Battery Replace-able



- ❖ BLE sensor reader / receiver
- Asset tracking
- ❖ Access control management
- Advertisement promotion
- Indoor location and position
- People Tracking
- ❖ IoT related
- Active RFID



Technical Specifications:

Size/Weight	94mm*38mm*18mm/42g
Bluetooth	Bluetooth low energy 4.0/5.0
Frequency	2.45GHz
Support Protocols	Apple iBeacon, Eddystone URL, Eddystone UID, Eddystone TLM
Temperature Measurement Capability	Measurement Accuracy (-40°C ~70°C): ±0.3°C
Humidity Measurement Capability	Measurement Accuracy (0%RH~90%RH): ±5%RH with 0.05%RH



BLE 2.45GHz Active RFID Temperature | Humidity Tag

127044

Software Configurable 100ms to 10s
-40 ~ 4dBm
-40°C to 70°C / 10°C to 25°C
Max 95%, Non condensing, relative humidity
Internal / Replace-able 2600mAh ER14505 battery
IP63
Built-in















GAO Group GAORFID.com GAOTek.com

Toll Free (USA & Canada) 1-877-585-9555 All Other Areas +1 (289) 660-5590 sales@GAORFID.com