

Overview:

GAORFID SKU#127057 IP68 Waterproof Pallet & Crate beacon/tag operates at 2.45GHz, the SKU#127057 active tag is a new generation beacon that is loaded with Bluetooth 5.0 hardware platform, and supports to advertise standard iBeacon. The reading range between 127057 and compatible gateways/receivers could be up to 100 meters.

Main Features:

- ✓ Standard iBeacon, free band of 2.45GHz
- ✓ Bluetooth 4.0/5.0 chipset
- ✓ The max. 100 meters reading distance with SKU#217030 gateway or any other Bluetooth Featured devices (e.g. iPhones, Android smart devices, etc.)
- ✓ IP68 waterproof housing
- ✓ Built-in Temperature Sensor
- ✓ Optional Accelerometer/Vibration Sensor
- ✓ Optional NFC Chip
- ✓ Ultra-low power consumption chipset nRF52 series
- ✓ Long Battery life, up to 4 years



Applications:

- ❖ BLE sensor reader / receiver
- ❖ Asset tracking
- ❖ Access control management
- ❖ Advertisement promotion
- ❖ Indoor location and position
- ❖ People Tracking
- ❖ IoT related
- ❖ Active RFID

Technical Specifications:

Size/Weight	127mm*26mm*10mm / 32g
Bluetooth	Bluetooth low energy 4.0/5.0
Frequency	2.45GHz
Support Protocols	Apple iBeacon, Eddystone URL, Eddystone UID, Eddystone TLM

Beaconing Interval	Default 1000mS
Transmit power	0dBm
Operating / Storage temperature	-40°C to 70°C / 10°C to 25°C
Humidity	Max 95%, Non condensing, relative humidity
Battery	Non-replaceable 1000mAh Lithium battery (4 years of life time)
Waterproof	IP68
Accelerometer/Vibration Sensor	Optional
Temperature Sensor	Built-in - Accuracy: +/-1°C; measurement range: -40°C ~70°C



Eddystone



<p>GAO Group GAORFID.com GAOTek.com</p>	<p>Toll Free (USA & Canada) 1-877-585-9555 All Other Areas +1 (289) 660-5590 sales@GAORFID.com</p>
---	--