



This contactless thin RFID card is commonly used for ticketing and security systems.

GAO RFID Inc.'s high frequency RFID card is designed for ticketing and security systems. It is waterproof and dustproof and is resistant to immersion in salt water, alcohol, oil, 10% HCl and ammonia.

Technical Specifications

Frequency	13.56MHz
Type	Contactless read/write
Capacity	1kbit
Tested read range	2.5cm to 10cm
Multi-detection	Yes
Material	PVC
Compliance	MF1 S50
Operating temperature	-25°C to 70°C
Storage temperature	-40°C to 85°C
Dimensions	85.6mm × 53.98mm × 0.8mm (L × W × H)
Weight	5g ±0.5g
Resistance	Shock and vibration (depending on packaging)





GAO RFID Inc.

A Member of GAO Group

Celebrating Over 15 Year of Innovation

Product Overview

13.56MHz ISO MF1 S50 Thin RFID Tag (113303)



GAO Group

Celebrating Over 15 Years of Innovation

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

China: 86-519-80691090
86-519-80691089

sales@GAORFID.com