



This RFID vicinity reader can read multiple tags from a distance of up to 50cm under ideal conditions. It is a suitable hardware solution that can be integrated into access control, security control or admission control systems.

This portable adheres to ISO15693 UID and is both CE and FCC certified and can communicate with three different interfaces: 3 in 1 - RS232, Wiegand and MSR ABA TK2. It is waterproof and dustproof allowing for excellent performance even in harsh environments. Also, it requires Variable 6 – 12 VDC - 9 V DC, 150 mA power and the transponders compliant with LR1512 and ISO 15693 are available for this reader.



Applications

- ✓ UID access
- ✓ Admission

✓ Security



Technical Specifications

Display	None Internal Led and Buzzer
Power requirements	Variable 6 – 12 VDC - 9 V DC, 150 mA
Communications Interface	3 in 1 - RS232, Wiegand and MSR ABA TK2
Baud rate	19,200 bps N, 8, 1
Frequency	13.56 MHz
Read Write Distance	up to 50 cm. with ISO 15693 compliant transponders
Technical Certificates	CE, FCC
Dimensions	L 83 mm X W 47 mm X H 16 mm
Housing	ABS
Operating Specifications	Waterproof and dustproof – IP40
	Operating Temperature: 0°C to 60°C
	Storage Temperature: -20°C to 70°C
	Humidity: 10 %to 90 % relative
Multi-Detection	Yes
Max read quantity	16 tags/sec
Antenna Compatibility	none required built in
Antenna Connection	none required
Transponder Compatibility	Tag-it at HF-I ICODE SLI, LR1512, my d vicinity, ISO 15693
	Compliant Transponders
Additional Features	Linear regulator recommended









GAO Group

Celebrating Over 15 Years of Innovation

GAORFID.com
GAOTek.com
GAORFIDAssetTracking.com
GAOComm.com
GAOInstruments.com
GAOFiberOptics.com
GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales Ext.602 for Other Inquiries

China: 86-519-80691090

86-519-80691089

sales@GAORFID.com