

***This high frequency RFID antenna enables long read range of up to 75 cm with single antenna and up to 130 cm with double antennas.***

This high frequency RFID antenna is compliant with ISO15693 and ISO18000-3 protocols and features an easy installation mounting kit, SMA connector and ABS protection. It enables a long read range of up to 75 cm with single antenna and up to 130 cm with dual antennas. This antenna is suited to applications such as industrial auto control system, production tracing, goods and livestock identification, and document management.

### **Key Features**

- ✓ Operating frequency: 13.56 MHz
- ✓ Compliant with ISO15693 and ISO18000-3 protocols
- ✓ Long reading distance; able to read up to 130 cm with double antennas
- ✓ Easy installation mounting kit



### Technical Specifications

Operating Frequency	13.56 MHz
Protocol	ISO15693, ISO18000-3
Connector	SMA
Max. Power	6 W
Impedance	50Ω
Read Range	Single antenna: 75 cm Double antenna: 130 cm
Size	832 x 612 x 30 mm
Operation Temperature	-20 °C to 60°C
Storage Temperature	-25 °C to 70°C
Material	ABS
Color	White
Weight	3.2 kg

<p><b>GAO Group</b></p> <p><a href="http://GAORFID.com">GAORFID.com</a> <a href="http://GAOTek.com">GAOTek.com</a> <a href="http://GAOResearch.com">GAOResearch.com</a></p>	<p>Toll Free (USA &amp; Canada)</p> <p><b>1-877-585-9555</b></p> <p>All Other Areas</p> <p>416-292-0038</p> <p>Dial Ext.601 for Sales Ext.602 for Other Inquiries</p> <p><a href="mailto:sales@GAORFID.com">sales@GAORFID.com</a></p>
---	---