

This low frequency handheld RFID reader is an ideal device for animal identification and management.

This low frequency handheld RFID reader is an ideal device for animal identification and management. It is also an excellent choice for other applications such as logistics, field service, personnel tracking or event management. This reader features fast and accurate scanning and meets ISO11784/85, FDX-A and EMID standards. It uses a USB interface to connect with a computer for data exchange.



Key Features

- ✓ Meets ISO11784/85, FDX-A and EMID standards
- ✓ Large memory capacity
- ✓ USB interface
- ✓ Easy operation and high stability
- ✓ OLED screen for clear result display

Applications

- ✓ Logistics
- ✓ Field Service
- ✓ Animal Tracking
- ✓ Asset Tracking
- ✓ Access Control

Technical Specifications

| | |
|--------------------------|---|
| Working Frequency | 134.2 kHz |
| Tag Compatibility | EMID, FDX-B(ISO11784/85), FDX-A |
| Read Distance | 2 mm * 12 mm Glass Tube Tag: >18 cm 30 mm Animal Ear Tag: >25 cm |
| Read Time | < 100 ms |
| Screen | 128 * 64 OLED |
| Power | 4.5 V |
| Consumption | Work: 0.9 W; Standby: 0.3 W |
| Data memory | about 4000 items |
| Memory Time | > 20 years |
| Interface | USB 2.0, 2.4 G Wireless communication (Optional) |
| Weight | 300 g (without battery) |
| Operating specifications | Operating at 0 °C to 50 °C Storage at -30 °C to 70 °C |

| | |
|---|---|
| <p>GAO Group</p> <p>GAORFID.com</p> <p>GAOTek.com</p> <p>GAOResearch.com</p> | <p>Toll Free (USA & Canada)</p> <p>1-877-585-9555</p> <p>All Other Areas</p> <p>416-292-0038</p> <p>Dial Ext.601 for Sales Ext.602 for Other Inquiries</p> <p>sales@GAORFID.com</p> |
|---|---|