



This low frequency, fixed reader is well suited for continuously operation in harsh environments such as feeding stations, animal scales and sorting gates.

This RFID reader is compliant with ISO11784/5 standard and communicates with computer through RS232 or RS485 interface. Its patented auto-tuning function and diagnosis modules enable on-site set-up and diagnosis for noise problems, which makes it unique and outstanding among the readers in this class. The reader also supplies a synchronous clock enabling applications where several readers or antennae are used in close proximity. This fixed RFID reader has a durable case with an IP54 protection rating, and its integrated LEDs and function key provide for ease of operation. The reader also supplies a clock synchronization enabling applications where several readers or antennae are used in close proximity.



Key Features

- ✓ Optional synchronous clock
- ✓ Performs well even in the worst conditions
- ✓ Transponders with widespread H4102 chip can be read (optional)
- ✓ Able to read all FDX-B and HDX RFID transponders
- ✓ On-site set-up and diagnosis for noise problems



Main Specifications

Frequency	134.2 kHz
Transponder Types	HDX compatible (ISO 11784/5) FDX-B compatible (ISO 11784/5) H4002 compatible (optional)
Read Range (with antenna 312001)	Up to 80 cm with HDX transponder of Ø 30 mm Up to 60 cm with FDX-B transponder of Ø 30 mm
Interfaces	RS232 or RS485
Power Supply	12 V DC, 400 mA, linear
Temperature Range	0 °C to 60 °C
Dimensions	175 mm x 135 mm x 90 mm (L x W x H)
Weight	Approximately 500 g





GAO RFID Inc.

A Member of GAO Group

Celebrating Over 15 Year of Innovation

Product Overview

134.2 kHz Stationary RFID Reader (212002)



GAO Group

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com