

This long range read-only RFID tag offers reliable RF signal and communication distance even in RF unfriendly environments.

This 433 MHz active RFID tag possesses many outstanding features including a compact size, long read distance, low power consumption, high anti-interference, dust and water proof. It offers reliable RF signal and communication distance even in unfriendly RF environments. This read-only tag provides a long read range of up to 150 m and can be well deployed in personnel identification and location, asset tracking, process monitoring and vehicle management.



Key Features

- ✓ Long read distance
- ✓ Expandable memory
- Anti-collision

- Low power consumption and long lifespan
- RSSI field detection function
- Low power warning

Applications

- ✓ Personnel identification and location
- ✓ Livestock management

- ✓ Vehicle management
- Harbor management



Technical Specifications

Operating Frequency	433 MHz
Read Distance	Maximum 150 m in open air
Memory Capacity	128 byte, Expandable
Battery Lifespan	>5 years (one RF transmission per second), low power warning
Power Down Retention Period	More than 10 years
ID Number	32 bit
Modulation	2-FSK
Communication Baud Rate	250 kbps
Package	ABS
Dimension	86 mm × 55 mm × 4 mm (L×W×H)
Operation Temperature	-20 °C to 60 °C
Storage Temperature	-40 °C to 80 °C

GAO Group	Toll Free (USA & Canada) 1-877-585-9555
<u>GAORFID.com</u> <u>GAOTek.com</u> <u>GAOResearch.com</u>	All Other Areas
	416-292-0038
	Dial Ext.601 for Sales Ext.602 for Other Inquiries
	sales@GAORFID.com

433 MHz Active RFID Tag 124057 www.GAORFID.com