

This UHF Gen 2 RFID zip tie tag provides incomparable precision for the tracking of smaller high-value assets.

This RFID zip tie tag operates over a frequency range of 860 MHz to 960 MHz and provides a wide read distance of 3 to 5 meters depending on the working environment and reader. The tag is especially suitable for supply chain solutions and achieves 99.99% accurate read rates. It provides incomparable precision for the tracking of high-value assets such as electronic devices, communications/ network cards or servers.

Key Features

- ✓ Fast read rates
- ✓ EPC Class 1 Gen2 compliant
- ✓ Long read range
- ✓ IT asset identification
- ✓ Product tracking during manufacturing
- ✓ Tool tracking



Technical Specifications

Operating Frequency	860 MHz to 960 MHz
Standard	EPC Class 1 Gen 2
Operating Mode	Read/Write
Memory	96 bits
Read Distance	Approx. 3 m to 5 m (Depending on working environment and reader)
IC	NXP UCODE G2XL
Programming Cycles	100000 times
Data Retention	> 10 years
Packaging Material	Polypropylene random copolymer
Antenna Material	Copper
Backing Material	PET
Size	23.5 cm × 2.7 cm (L × W)
Operating Temperature	-40 °C to 65 °C
Storage Temperature	-40 °C to 85 °C

<p>GAO Group</p> <p>GAORFID.com</p> <p>GAOTek.com</p> <p>GAOResearch.com</p>	<p>Toll Free (USA & Canada)</p> <p>1-877-585-9555</p> <p>All Other Areas</p> <p>416-292-0038</p> <p>Dial Ext.601 for Sales Ext.602 for Other Inquiries</p> <p>sales@GAORFID.com</p>
---	---