

This highly stable and durable RFID container tag can be well deployed in many applications such as logistics, asset tracking, inventory management and warehouse management.

This highly stable and durable RFID container tag is compliant with ISO/IEC 18000-6C standard and can be used in many applications such as logistics, asset tracking, inventory management and warehouse management. It has an anti-collision function and is waterproof and protected from corrosion. This tag is designed with card buckle and a saw to the tie strip resulting in tight, secure connection to assets.



Key Features

- ✓ Long read range
- ✓ ISO/IEC 18000-6C compliant
- ✓ High durability and stability
- ✓ Anti-collision function
- ✓ Corrosion protection
- ✓ Waterproof

Applications

- ✓ Logistics
- ✓ Inventory management
- ✓ Asset tracking
- ✓ Warehouse management

Technical Specifications

Material	PP plastics	
Dimension	Size of Label	105mm×30mm×2.7mm
	Size of Tie Rod	210mm×5.3mm×2mm
	Total Length	315mm
Chip	Alien H3 (Other types of chip can be customized)	
Operating Frequency	915 MHz (ISO/IEC 18000-6C)	
Operation Temperature	-30 °C to 85 °C	
Identification Distance	Equipment read range: 10– 12m; handset read range: 2-3m. (reader dependent)	
Tension	250– 300N	
Locking Force	210-230N	

<p>GAO Group</p> <p>GAORFID.com</p> <p>GAOTek.com</p> <p>GAOResearch.com</p>	<p>Toll Free (USA & Canada)</p> <p>1-877-585-9555</p> <p>All Other Areas</p> <p>416-292-0038</p> <p>Dial Ext.601 for Sales Ext.602 for Other Inquiries</p> <p>sales@GAORFID.com</p>
---	---