



This Automatic Tour Patrol RFID Reader uses Swiss EM sensor card-reading technology. It is widely used in residential building property security patrol management and in field services maintenance

The RFID reader performs inductive card-reading with a response time of less than 0.1 s. It has a large memory capacity which can store 7200 records that can be quickly uploaded to a computer. It is designed to be resistant to water, shock and high or low temperature resistant. The reader communicates with a computer via COM port or USB interface.

Key Features

- ✓ Portable and light weight
- ✓ Large memory capacity
- ✓ Less than 0.1 s response time
- ✓ High security and low power consumption
- ✓ Fast download speed





Technical Specifications

Card-reading Mode	Inductive card-reading
Storage Capacity	7200 records
Response Time	less than 0.1 s
Indicate Mode	LED + LCD
Display Mode	96*64 LCD
Dimension	142 mm ×35 mm
Weight	260 g
Baud Rate	19200
Operating Temperature	-20 °C to 70 °C
Humidity Range	30% to 90%
Power Consumption	30 mA
Battery	3.6 V rechargeable Lithium battery
Standard Accessories	Lithium cell, data cable,leather sheath and battery charger

GAO Group

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com