

This biometric RFID terminal provides multiple authentication methods including facial, fingerprint, RFID and password.

This biometric RFID terminal is equipped with a 630 MHz high speed Multi-Bio processor and a high definition infrared camera enabling user identification even in dark environments. This terminal features a large memory capacity and high definition. An optional built-in 2000 mA backup battery provides 4 hours of continuous operation if the outside power source is unavailable. This device connects to a computer through RS232/RS485 interfaces. Additionally, its optional built-in Wi-Fi or GPRS are available for wireless communication.



Key Features

- ✓ Authentication methods include fingerprint, facial, RFID and password
- ✓ Ergonomic design, easy operation
- ✓ 4.3" TFT touch screen, simple interface
- ✓ Infrared optical system enables user identification even in dark environments
- ✓ Web-server management software
- ✓ Optional built-in backup battery provides extra 4 hours continuous operation
- ✓ Optional built-in Wi-Fi or GPRS for wireless communication

Technical Specifications

CPU	Multi-Bio 600
Camera	High Resolution Infrared Camera
Display	4.3" TFT touch screen
Face Capacity	500
Fingerprint Capacity	3000
Logs Capacity	100,000
Authentication Method	Fingerprint, Password+ Fingerprint, Fingerprint +Facial + Password
Communication	TCP/IP, RS232, RS485
Back-up Battery	2000 mA
Optional Functions	Wi-Fi, GPRS, Serial Printer, Mifare/HID/iClass card, Wiegand, Work Code
Wiegand Signal	Output
Power Supply	12 V 3 A
Verification Speed	≤2 s
Operating Temperature	0 °C to 45 °C
Operating Humidity	20 % to 80 %

GAO Group

GAORFID.com
GAOTek.com
GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com