

This desktop ultra high frequency RFID reader/writer is compliant to ISO18000-6C EPC Gen 2 protocol and operates at a range of 840 to 960 MHz.

The desktop RFID reader/writer is compliant to ISO18000-6C EPC Gen 2 protocol and operates at a frequency range of 840 to 960 MHz. It is specially designed for applications such as system logger, time and attendance, prepayment and ticket management. It features a compact housing design making it ideal for installation in environments with space constraints.



Key Features

- ✓ ISO18000-6C, EPC Class 1 Gen 2
- ✓ Available with slot or flat reading surfaces
- ✓ Features LED and Beep sound indications
- ✓ Frequency range: 840- 960MHz
- ✓ Two communication interfaces: RS232 or USB

Technical Specifications

Interface	RS232 (serial COM PORT) USB (Virtual COM PORT) USB (Human Interface Device (HID) Keyboard Mode)
DC Power	5 VDC
RFID Protocol	EPC Class1 Gen2 / ISO 18000-6C
Frequency	840 MHz to 960 MHz
Read Range	5 to 30 cm
Temperature Range	Operating Temp: -0 °C to+55 °C
Humidity	10% to 85% Non-condensing
Dimensions W × L × D	65 mm × 100 mm × 24.7 mm

GAO Group

GAORFID.com
GAOTek.com
GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com