



This flexible UHF Gen2 Metal-Mount RFID tag is widely used in applications such as asset tracking and supply chain applications.

This flexible UHF Gen2 mount-on-metal RFID tag is ideal for both indoor conditions and for basic outdoor use. It is suitable for multiple applications such as asset tracking and supply chain applications. The thin RFID tag operates over the frequency range of 902 to 928 MHz for North America and 865 to 868 MHz for Europe. It is compliant with EPC Class1 Gen2 standard and has an outstanding read range of 2.5 to 5 m when used directly on metal. This small form factor tag is available with EPC encoding, barcode, and human readable content. It is also available with pressure sensitive adhesive.



Key Features

- ✓ On metal RFID tag and human readable content
- ✓ Compliant with EPC Class1 Gen2 standard
- ✓ Available with paper or polyester labels
- ✓ Ideal for asset tracking applications like laptop computers, tools, and electronic components.
- ✓ Available with custom label 4-colorprinting
- ✓ Available with pressure sensitive adhesive
- ✓ Small form factor, thin, and flexible
- ✓ Available with EPC encoding, barcode,



Technical Specifications

Frequency	UHF
Patrol	EPC Class1 Gen2
Read Range	2.5 m to 5 m (8 ft to 15 ft)
Operating Temperature	-40 °C to 80 °C
Weight	11 g
Size	54 mm x 16 mm x 4.3 mm (2.15 in x 0.625 in x 0.170 in)
Mounting	Adhesive



GAO Group

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com