

This passive Gen 2 UHF RFID tag provides improved visibility of assets and high efficiency in various environments.

The Flex is a passive Gen 2 UHF EPC Class 1 RFID tag providing improved visibility of assets and high efficiency in various environments. With an excellent performance-to-size ratio, the Flex RFID tag has a read range over 16.5 feet and ensures accurate asset registration along with security benefits. It is also available in a low-profile ruggedized rigid case for use in harsh environments



Applications

- ✓ Asset Monitoring such as Laptop tracking
- ✓ Shelf-edge retail and warehouse location
- ✓ Tool tracking
- ✓ Automotive parts and components tracking

Features

- ✓ Robust, balanced performance on, off, or near metals and liquids
- ✓ Fast read speeds and reliable read rates of over 99.99%
- ✓ Excellent price to performance ratio
- ✓ Improved efficiency for locating or auditing items
- ✓ 240 bit EPC global Class 1 Gen 2 compliant silicon
- ✓ Minimal support requirements
- ✓ Supplied with label finish or optional ruggedized case finish



Specifications

Frequency	902MHz to 928MHz
IC	Alien Higgs H2
IC Protocol	UHF EPC Class 1 Gen 2
IC Memory	240bits
Read Range on Metal	> 16.5ft
Read Range off Metal	> 16.5ft
Operating Temperature	-4°F to 149°F
Attachment	3M 9742LE self adhesive
Dimensions	3.0inch (L) x 0.6inch (W) x 0.1inch (L x W x H)
Housing	Laminated label
Weight	0.09oz
Color	White





GAO Group

Celebrating Over 15 Years of Innovation

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Ext. 601 for Sales

Ext. 602 for Other Inquiries

China: 86-833-2419625

sales@GAORFID.com