

This position marker is specially used to determine exact locations of specially equipped Sensor SMART tags.

This position marker is specially used to determine exact locations of specially equipped tags. As the tag passes the induction loop connected to the position marker, identification data from the position marker is downloaded onto the tag. Depending on the type of tag, current as well as previous IDs and the relative time of passage over the loop are either repeatedly broadcast or they can be read from the tag by a reader at a later time and place. It has the ability to control inductive field limits and vehicle lane discrimination and direction recognition can be realized. The position marker is typically mounted near the induction loop and remains maintenance-free after setting the original parameters.





Technical Specifications

Communication Data Inductive Loop	
Compatibility	ILR [®] i-Q and i-B Tags with Marker feature
Frequency	125 kHz
Modulation	100% AM
Range (adjustable)	up to 3.5 m
Position Data	16 bits (programmable)
Loop Current	Max. 6 App
Loop Area	Integrated
Pass-over Velocity	Max. 100 km/h
Number of Loops	1 (internal)
User Interface	
Bus	i-BUS (RS422)
Manual	Bluetooth, Class 2, SPP Profile
Indicators	4 LEDs, bicolor (Run, Loop, Bus, Error)
Features	Programmable Loop ID, adjustable Loop current (range), Loop diagnosis
Electrical	
Supply Voltage	10 – 30 VDC / 85 – 265 VAC*
Power Consumption	Max. 20 W
* AC supply available in Europe only	
Environmental	
Operating temperature	-30 °C to +55 °C / -22 °F to +131 °F
Storage temperature	-40 °C to +80 °C / -40 °F to +176 °F
Certification/EMC	EN 300 220 (EC); FCC Part 15 (US)

www.GAORFID.com



Physical

,	
Dimensions	Unbalance L9, impedance 75 Ω / High impedance >2K Ω
	Balance RJ48, impedance 75 Ω / High impedance >2K Ω
Enclosure	Plastic / Aluminium
Weight	800 g
Enclosure Rating	IP 54
Cable feed	1 x M16 feed through,
	2 x cable spouts (i-BUS, opt.)

GAORFID.com GAOTek.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales Ext.602 for Other Inquiries

sales@GAORFID.com

Position Marker 491013 www.GAORFID.com