



The ultra high frequency magnetic RFID tag is useful for corrugated cardboard cases and plastic bottles.

The passive magnetic RFID tag is useful for corrugated cardboard cases and plastic bottles. This high-performance RFID tag is available as continuous web or with adhesive backing and different face materials. It supports multi-detection and has a tested read range of up to 10m. Encapsulated with ABS engineering plastic, this passive RFID tag is waterproof and dustproof and is resistant to immersion in salt water, alcohol, oil, 10% HCL ammonia.



Technical Specifications

Type	Contactless Read Only
Operating Frequency	US (902-928Mhz) (UHF-Ultra High Frequency)
Capacity	64 bits ID
Common Usage	Reusable magnetic tag
Standard Deployment	Corrugated cardboard cases, plastic bottles
Tested Read Range	0 to 10m
Multi-Detection	Yes
Size	226mm x 38mm x 23.6mm
Material	ABS Engineering Plastic
Color	Black
Regulatory Specifications	ISO18000-6B
Additional Features	Also available as continuous web or with adhesive backing and different face materials
Resistance	Shock- Dependant on packaging; Vibration – Dependant on packaging
Operating Temperature	-25°C to 70°C
Storage Temperature	-40°C to 85°C



GAO RFID Inc.

A Member of GAO Group

Celebrating Over 15 Year of Innovation

Product Overview

UHF Magnetic RFID Tag - Passive (116005)



GAO Group

Celebrating Over 15 Years of Innovation

GAORFID.com
GAOTek.com
GAORFIDAssetTracking.com
GAOComm.com
GAOInstruments.com
GAOFiberOptics.com
GAOEmbedded.com
GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

China: 86-519-80691090
86-519-80691089

sales@GAORFID.com